

MATRAX AGRI CLASSIC 20W30**Description**

Universal Tractor Transmission Oils (UTTO) multigrade lubricant.

Application

Especially developed for application in transmissions, hydraulic systems, oil brakes and other ancillary systems suitable for agricultural tractors and off-road equipment. Ensures high levels of wear protection at start-up and in operation, with enhanced corrosion protection properties.

Technical characteristics

Good thermal stability: good performance in wide temperature ranges and adverse conditions, preventing the formation of deposits and sludge
Corrosion resistance: additives that reduce chemical attacks on metallic surfaces by organic acids resulting from exposure to contaminants that oxidise the oil, ensuring long service lives
Convenient for the operator: excellent fluidity at low temperatures that results in a smooth performance during gearshifts from low temperatures at start-up to the highest operating temperatures

Technical information**Parameter**

	MATRAX AGRI CLASSIC 20W30
Kinematic viscosity @40°C (cSt) ASTM D 445	88,5
Kinematic viscosity @100°C (cSt) ASTM D 445	12,1
Viscosity index ASTM D 2270	130
Density a 15°C (g/cm ³) ASTM D 1298	0,871
Flash point (°C) ASTM D 92	225
Freezing point (°C) ASTM D 97	-25

Approvals and Recommendations

API GL-4 · Allison C -4 · John Deere JDM J20C/J20D · Massey Ferguson CMS M1135/M1143/M1145 · CNH MAT 3525 (Ford M2C-134D) · CNH MAT 3526 · VOLVO WB 101 · Caterpillar TO-2 · Case MS 1209/1207/1206/1204 · Eaton M2950S · JCMAS HK P-041

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.