

MATRAX AGRI SINTESIS 10W40**Description**

STOU (Super Tractor Oil Universal) synthetic multigrade lubricant.

Application

Especially developed for application in engines, transmissions, hydraulic systems, oil brakes and other ancillary systems suitable for agricultural tractors and off-road equipment.

Ensures high levels of wear protection at start-up and in operation, with enhanced corrosion protection properties.

Technical characteristics

Maintenance made simple: one lubricant that can be used in all the equipment

Good thermal stability: good performance in wide temperature ranges and adverse conditions, preventing the formation of deposits and sludge

Corrosion resistance: additives that reduce chemical attacks on metallic surfaces by organic acids resulting from exposure to contaminants that oxidise the oil, ensuring long service lives

Convenient for the operator: excellent fluidity at low temperatures that results in a smooth performance during gearshifts from low temperatures at start-up to the highest operating temperatures

Technical information**Parameter**

Kinematic viscosity @40°C (cSt) ASTM D 445
Kinematic viscosity @100°C (cSt) ASTM D 445
Viscosity index ASTM D 2270
Density a 15°C (g/cm³) ASTM D 1298
Flash point (°C) ASTM D 92
Freezing point (°C) ASTM D 97

MATRAX AGRI SINTESIS 10W40

103,5
14,5
140
0,867
220
-25

Approvals and Recommendations

API CG-4 · ACEA E3 · API GL-4 · Allison C-4 · John Deere JDM J27 · Massey Ferguson M1145/1144/1139 · Ford ESN M2C-159-C/M2C-159-B · ZF TE-ML 06A/06B/06C/07B · Caterpillar TO-2 · New Holland 82009201/82009202/82009203 · Eaton M2950S

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.