

MATRAX SINTESIS 4T 10W40**Description**

Synthetic lubricant for vehicles equipped with 4-stroke engines

Application

High-quality synthetic lubricant especially recommended for vehicles equipped with 4-stroke engines requiring compliance with the JASO MA/MA2 standard. Developed with highly refined bases, it includes a state-of-the-art additive package to ensure maximum protection in medium and high-powered engines.

Technical characteristics

Enhanced lubricant longevity: exceptional thermal stability and resistance to oxidation, even at high temperatures or under adverse conditions, preventing the formation of deposits and sludge

Exceptional cold-start performance: excellent fluidity at low temperatures

Engine protection: its high Viscosity Index guarantees that the lubricant film survives even at high operating temperatures

Reduced clutch wear: due to its state-of-the-art friction additives, it effectively reduces clutch disc wear

Technical information**Parameter**

Kinematic viscosity @40°C (cSt) ASTM D 445
Kinematic viscosity @100°C (cSt) ASTM D 445
Viscosity index ASTM D 2270
Density a 15°C (g/cm³) ASTM D 1298
Flash point (°C) ASTM D 92
Freezing point (°C) ASTM D 97

MATRAX SINTESIS 4T 10W40

90,3
13,2
158
0,863
218
-30

Approvals and Recommendations

JASO MA/MA2 (T903:2016) · API SN

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.