

# MATRAX ANTIFREEZE G12 - 50

## Description

Organic antifreeze / coolant of the OAT type with 50% dilution, ethylene glycol based, recommended for use in the cooling circuits of light and heavy vehicles.

## Application

Its formulation with ethylene glycol and a modern additive package gives the product excellent protective capacity for all the components of the cooling circuit that equip internal combustion engines.

Especially recommended for circuits in large commercial vehicles and large engines.

For direct use in the cooling circuit.

## Technical characteristics

Excellent anti-corrosion, anti-rust and anti-foam properties

Organic technology inhibitors: protection against corrosion of all metals thanks to the inhibitors in the formulation

Compatibility: with gaskets and elastomers

Protection against cavitation: prevents the formation of bubbles

Prevents the formation of deposits: due to the presence of demineralised water in its composition

## Technical information

### Parameter

Colour

ethylene glycol concentration

pH

Density a 20°C [g/cm<sup>3</sup>] ASTM D 1298

Freezing point [°C] ASTM D 97

Freezing point [°C] ASTM D 97

### MATRAX ANTIFREEZE G12 - 50

Verde/Green/Vert

1

8

1,07

-33 (quando diluido a 50%)

158 (quando diluido a 50%)

## Approvals and Recommendations

VW TL 774 D (G-12) · UNE 26 361 · SAE J 1034/J 814 · FORD WSS M 97B44D · MIL A 46153 C · MB 326.3 · MAN 324 TYPE SNF

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.