

MATRAX DAW FLUID

Description

Synthetic hydraulic fluid for vehicles with hydropneumatic shock absorbers and suspensions, as well as centralised hydraulic circuits.

Application

Synthetic hydraulic fluid formulated with additives that improve the Viscosity Index. Also used in DSG automatic transmissions (AUDI, VW, SEAT, CITRÖEN and BMW.), ensuring long-lasting system performance.

Technical characteristics

Low viscosity: to ensure suspension, power steering and braking functions at very low temperatures.

High Viscosity Index: which gives it good thermal stability

Technical information

Parameter	MATRAX DAW FLUID
Kinematic viscosity @100°C (cSt) ASTM D 445	6,2
Viscosity index ASTM D 2270	326
Density a 15°C (g/cm ³) ASTM D 1298	0,846
Flash point (°C) ASTM D 92	>110
Freezing point (°C) ASTM D 97	-51
Appearance	Fluido cor verde

Approvals and Recommendations

VW TL 521 46 · PSA S712710 · MB 345.0 · MAN 3289

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.