

# MATRAX INFLUX V-REO 5W40

## Description

Fully synthetic, REO (Robust Engine Oil) lubricant for use in Volkswagen group petrol or diesel engines requiring compliance with the VW 508.88 and VW 509.99 specifications.

## Application

Especially versatile, it has been developed for passenger vehicles equipped with petrol or diesel engines requiring an REO (Robust Engine Oil) lubricant. The careful selection of the synthetic bases and additives used in its formulation was developed especially for Volkswagen Group engines that operate under very adverse conditions, namely with fuels with a high content of ethanol, methanol and/or a high content of sulphur and require compliance with the VW 508.88 and VW 509.99 specifications.

It is also recommended for use in petrol and diesel engines operating under very adverse conditions for which the manufacturer recommends a 5W40 grade compliant with the ACEA A3/B4 or API SN standards. It should not be used in engines with exhaust gas after-treatment systems.

## Technical characteristics

Fuel economy: and consequent reduction of CO2 emissions  
Protection under adverse conditions: prepared for use with fuels with high ethanol, methanol and/or high sulphur content  
Outstanding cold-start performance: excellent fluidity at low temperatures  
Low lubricant consumption: particularly resistant to high temperatures and oxidation, it limits the formation of deposits and reduces wear, enabling a reduction in lubricant consumption

## Technical information

### Parameter

Kinematic viscosity @40°C (cSt) ASTM D 445  
Kinematic viscosity @100°C (cSt) ASTM D 445  
Viscosity index ASTM D 2270  
Density a 15°C (g/cm<sup>3</sup>) ASTM D 1298  
Flash point (°C) ASTM D 92  
Freezing point (°C) ASTM D 97  
Sulphated ashes (%) ASTM D 874  
TBN (mg KOH/g) ASTM D 2896

### MATRAX INFLUX V-REO 5W40

75,9  
13,3  
179  
0,855  
215  
-42  
1,14  
11,3



## Approvals and Recommendations

ACEA A3/B4 · API SN · MB 229.5 · VW 508.88 / 509.99 · Renault RN 0700 / 0710 · Porsche A40

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.