



MATRAX MOLDAX MG

Description

Mineral-based lubricant, formulated with antioxidant and anti-corrosive additives, especially developed for concrete formwork operations using metal or wooden moulds.

Application

It is a product that facilitates formwork removal, providing smooth and shiny surfaces, thereby preventing the formation of roughness and stains on the concrete surface.

Its use is recommended for demoulding and formwork removal of concrete, artificial stone, simple parts, beams, prefabricated elements, etc.

It is used undiluted or mixed with water at a dilution ratio between 5% to 10%.

Its use is recommended for demoulding and formwork removal of concrete, artificial stone, simple parts, beams, prefabricated elements, etc.

Apply using a brush, sponge, or spray, ensuring a uniform film on the mould.

Technical characteristics

Good mould-release properties: providing an excellent surface finish and preventing adhesion to the metal mould, regardless of the complexity of the shape

Antioxidant performance: acts against oxidation, forming a protective film on the mould and shielding it from corrosion, thus facilitating its preservation and extending its lifespan



MATRAX MOLDAX MG

Technical information

Parameter	<u>215</u>	<u>230</u>
Kinematic viscosity @100°C (cSt) ASTM D 445	4,3	11
Viscosity index ASTM D 2270	95	95
Density a 15°C (g/cm ³) ASTM D 1298	0,868	0,889
Flash point (°C) ASTM D 92	205	230
Freezing point (°C) ASTM D 97	-9	-9
0	Pass	Pass
0	Pass	Pass

Approvals and Recommendations

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.