



MATRAX SAW CHAIN PLUS

Description

Lubricant for chainsaw chains.

Application

Formulated from refined base oils and with carefully selected additives that provide it with great adherence to the surface to be lubricated.

Especially designed with high viscosity, this product provides high performance, resulting in reduced oil consumption, excellent surface adhesion, high oxidation resistance, and exceptional corrosion protection.

Technical characteristics

Thermal stability: allows its use over extended temperature ranges except in environments with high temperature gradients

Corrosion resistance: additives that reduce chemical attacks on metal surfaces by organic acids resulting from exposure to contaminants that oxidise the oil, providing extended periods of use

Excellent adhesiveness: adheres to surfaces very effectively, ensuring better lubrication of cutting tools



MATRAX SAW CHAIN PLUS

Technical information

Parameter	<u>150</u>
Kinematic viscosity @40°C (cSt) ASTM D 445	150
Kinematic viscosity @100°C (cSt) ASTM D 445	16
Viscosity index ASTM D 2270	110
Density a 15°C (g/cm ³) ASTM D 1298	0,833
Flash point (°C) ASTM D 92	255
Freezing point (°C) ASTM D 97	-9

Approvals and Recommendations

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.