

# MATRAX INFLUX 0W30 ECO

## Description

Next-generation, fully synthetic lubricant for use in new engines requiring compliance with the BMW Longlife-12FE or Ford WSS M2C950-A specifications.

## Application

Especially developed for light passenger vehicles equipped with high-performance petrol or diesel engines requiring compliance with the BMW Longlife-12FE and Ford WSS M2C950-A specifications. It creates a very resistant lubricant film, facilitating cold starts, reducing friction in the engine as well as the operating temperature and keeping oil pressure stable. It is also recommended for use in petrol and diesel engines for which the manufacturer recommends a 0W30 grade compliant with the ACEA C2 or the API SN Plus standards.

## Technical characteristics

Extended service intervals: allows for extended service intervals and is compatible with the extended maintenance service system (WIV)

Fuel economy: and consequent reduction in CO<sub>2</sub> emissions  
Outstanding cold-start performance: excellent fluidity at low temperatures

Protection of exhaust gas after-treatment systems: its low contents of sulphated ash, phosphorus and sulphur (Low SAPS) allow for optimal cleaning of particulate filters, SCRs, EGRs and/or catalytic converters

Low lubricant consumption: particularly resistant to high temperatures and oxidation, it limits the formation of deposits and reduces wear, enabling a reduction in lubricant consumption

## Technical information

### Parameter

Kinematic viscosity @40°C (cSt) ASTM D 445  
Kinematic viscosity @100°C (cSt) ASTM D 445  
Viscosity index ASTM D 2270  
Density a 15°C (g/cm<sup>3</sup>) ASTM D 1298  
Flash point (°C) ASTM D 92  
Freezing point (°C) ASTM D 97  
Sulphated ashes (%) ASTM D 874  
TBN (mg KOH/g) ASTM D 2896

### MATRAX INFLUX 0W30 ECO

58  
10,8  
181  
0,64  
215  
-48  
0,77  
9,45



## Approvals and Recommendations

ACEA C2 · ACEA A5/B5 · API SP/SP-RC · MB 227.61/229.61 · BMW LL-12FE · Ford WSS-M2C950A · ILSAC GF-6

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.