

**MATRAX COOLANT 20%****Description**

Organic antifreeze / coolant with 20% dilution for direct use in passenger car and heavy duty vehicles cooling circuits.

**Application**

Its formulation based on ethylene glycol and a modern additive package gives the product excellent protective capacity for all the components of the cooling circuit that equip internal combustion engines.

Especially recommended for circuits in large commercial vehicles and large engines.

For direct use in the cooling circuit.

**Technical characteristics**

Excellent anti-corrosion, anti-rust and anti-foam properties

Organic technology inhibitors: protection against corrosion of all metals thanks to the inhibitors in the formulation

Compatibility: with gaskets and elastomers

Protection against cavitation: prevents the formation of bubbles

Prevents the formation of deposits: due to the presence of demineralised water in its composition

**Technical information****Parameter**

Colour

ethylene glycol concentration

pH

Density a 20°C (g/cm<sup>3</sup>) ASTM D 1298

Freezing point (°C) ASTM D 97

Freezing point (°C) ASTM D 97

**MATRAX COOLANT 20%**

Verde/Green/Vert

0,2

7,9

1,02

-10

108

**Approvals and Recommendations**

BS6580-2010 · ASTM D3306 · ASTM D3321 · UNE 26361-88

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.