

MATRAX GEAR CLASSIC 85W140 GL-4

Description

Multigrade lubricant for use in manual gearboxes requiring compliance with the API GL-4 standard.

Application

Lubricant developed for application in synchronised manual gearboxes of heavy-duty vehicles. Its formulation ensures maximum performance and maximum protection, offering the best lubrication and a longer service life.

Technical characteristics

Excellent oxidation stability: even under extreme conditions, providing greater product durability
High anti-wear protection: which improves the durability of the mechanisms
Compatibility with most sealants and elastomers: it does not react chemically, preventing the formation of sludge

Technical information

Parameter	MATRAX GEAR CLASSIC 85W140 GL-4
Kinematic viscosity @40°C (cSt) ASTM D 445	385
Kinematic viscosity @100°C (cSt) ASTM D 445	29,5
Viscosity index ASTM D 2270	106
Density a 15°C (g/cm ³) ASTM D 1298	0,898
Flash point (°C) ASTM D 92	285
Freezing point (°C) ASTM D 97	-12

Approvals and Recommendations

API GL-4 · ZF TE-ML 07A

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.