

MATRAX GEAR CLASSIC 90 GL-5

Description

Multigrade lubricant for use in a wide range of automotive differentials requiring compliance with the API GL-5 standard.

Application

Lubricant developed for application in differentials subject to severe operating conditions. Its formulation ensures maximum performance and maximum protection, offering the best lubrication and a longer service life.

Technical characteristics

Excellent oxidation stability: even under extreme conditions, providing greater product durability
High anti-wear protection: which improves the durability of the mechanisms
Compatibility with most sealants and elastomers: it does not react chemically, preventing the formation of sludge

Technical information

Parameter

Kinematic viscosity @40°C (cSt) ASTM D 445
Kinematic viscosity @100°C (cSt) ASTM D 445
Viscosity index ASTM D 2270
Density a 15°C (g/cm³) ASTM D 1298
Flash point (°C) ASTM D 92
Freezing point (°C) ASTM D 97

MATRAX GEAR CLASSIC 90 GL-5

190
17,5
95
0,897
280
-12

Approvals and Recommendations

API GL-5 · MIL PRF-2105D · GB 13895-2018 · ZF TE-ML-07A

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.