

MATRAX HEAVY CLASSIC 40

Description

Monograde, mineral-based lubricant for diesel engines, available in SAE 30 grade

Application

Use only in diesel engines, hydraulic systems and transmissions for which monograde diesel lubricants are recommended.

Technical characteristics

Selected additive package: contains effective corrosion, oxidation and rust inhibitors, as well as additives to control foaming

Protection against wear and deposit formation: formulated to reduce both wear and deposit formation, thus controlling maintenance costs

Various applications: it can be used in hydraulic systems and transmissions requiring the use of a monograde lubricant

Technical information

Parameter

Kinematic viscosity @40°C (cSt) ASTM D 445
Kinematic viscosity @100°C (cSt) ASTM D 445
Viscosity index ASTM D 2270
Density a 15°C (g/cm³) ASTM D 1298
Flash point (°C) ASTM D 92
Freezing point (°C) ASTM D 97
Sulphated ashes (%) ASTM D 874
TBN (mg KOH/g) ASTM D 2896

MATRAX HEAVY CLASSIC 40

148,5
14,9
100
0,886
230
-18
0,81
7,13



Approvals and Recommendations

ACEA E2 · API CF-4 · MB 228.1 · MAN 271 · MTU Type 1

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.