

**MATRAX HEAVY CLASSIC 50 CF****Description**

Lubricant for diesel engines requiring compliance with the API CF standard

**Application**

Use only in diesel engines, hydraulic systems and transmissions for which monograde diesel lubricants are recommended.

**Technical characteristics**

Selected additive package: contains effective corrosion, oxidation and rust inhibitors, as well as additives to control foaming

Protection against wear and deposit formation: formulated to reduce both wear and deposit formation, thus controlling maintenance costs

Various applications: it can be used in hydraulic systems and transmissions requiring the use of a monograde lubricant

**Technical information****Parameter**

Kinematic viscosity @40°C (cSt) ASTM D 445  
Kinematic viscosity @100°C (cSt) ASTM D 445  
Viscosity index ASTM D 2270  
Density a 15°C (g/cm<sup>3</sup>) ASTM D 1298  
Flash point (°C) ASTM D 92  
Freezing point (°C) ASTM D 97  
Sulphated ashes (%) ASTM D 874

**MATRAX HEAVY CLASSIC 50 CF**

173  
17,5  
110  
0,891  
225  
-22  
0,8

**Approvals and Recommendations**

API CF

All packaging must be stored in covered facilities. In cases where outdoor storage is unavoidable, the drums should be placed horizontally to prevent the possible infiltration of water, as well as their deformation. Products should not be stored above 60°C, exposed to direct sunlight or low temperatures. We advise you to read the safety data sheet carefully for more information on its use and handling.